

### L20 external timber doorsets

#### NON FIRE RATED DOORSET

Core: 44mm ply faced solid core door  
Size: To client's specification  
Lippings: 8mm FSC® hardwood lipped 4 edges  
Finish: To client's specification  
Glazing: 6.4mm clear laminated glass Ahm Std.  
Glazing sizes: 0.72m2 maximum area  
Intumescent: N/A  
Weight: 50kg approx (based 2040 x 926)  
Lining: 45mm (15mm rebate) HW Ahm Std.  
Weatherseal: Aquamac 21 (stop recessed)

#### 30 MINUTE FIRE RATED DOORSET

Core: 44mm ply faced solid core door  
Size: To client's specification  
Lippings: 8mm FSC® hardwood lipped 4 edges  
Finish: To client's specification  
Glazing: 7mm Pyrobelite glass Ahm Std.  
Glazing sizes: 0.72m2 maximum area  
Intumescent: Lorient single fire strip  
Weight: 50kg approx (based 2040 x 926)  
Lining: 45mm (15mm rebate) HW Ahm Std.  
Weatherseal: Aquamac 21 (stop recessed)

#### 60 MINUTE FIRE RATED DOORSET

Core: 54mm ply faced solid core door  
Size: To client's specification  
Lippings: 8mm FSC® hardwood lipped 4 edges  
Finish: To client's specification  
Glazing: 16mm Pyrobel glass Ahm Std.  
Glazing sizes: 0.72m2 maximum area  
Intumescent: Lorient twin fire strips  
Weight: 65kg approx (based 2040 x 926)  
Lining: 45mm (15mm rebate) HW Ahm Std.  
Weatherseal: Aquamac 21 (stop recessed)

#### AVAILABLE OPTIONS

Double glazed 'Low E' units  
Bomb-blast glass  
Sandblast/opaque/obscured glass  
Mirrored & one-way glass  
DDA compliant aluminium threshold seals  
Finger guard safety systems  
Fire retardant air transfer grilles  
Face fixed timber weatherboards

# ahmarra

20 Fitzherbert Road

Farlington

t: 02392 389 076

Portsmouth

f: 02392 389 077

Hampshire

e: [gen@ahmarra.co.uk](mailto:gen@ahmarra.co.uk)

PO6 1SD

w: [www.ahmarra.co.uk](http://www.ahmarra.co.uk)