

Ahmarra Ironmongery

Mechanical Access Lock



PRODUCT SPECIFICATIONS

Our heavy duty mechanical access locks offer flexibility on how to manage entry - by key, code or code free access. Throwing the deadbolt on the mortice lock models will lock out code users when appropriate. A safety feature ensures that the inside lever handle will retract the deadbolt so as to avoid accidentally locking a person inside the room.


- Large full size lever handles with return to door
- PVD low maintenance finish
- Code free access options
- Suitable for internal and external use
- Mortice latch and mortice lock models available
- Tumbler alignment for easy code change
- Large three coil lever return spring suitable for high traffic use
- Available in stainless steel or polished brass finish
- Neoprene seals included
- Codelocks Fire Kit Packs can be fitted to latch locks for 30 or 60 minute fire doors
- Tested in accordance with BS EN 1634-1:2008

AHM-CL500 / CL505
Front & Back Plates



Front and back plates only. Use with existing mortice latch or lock. Existing lock must have a fixing hole 22mm (7/8") below follower (spindle).

AHM-CL15190 / CL515
Mortice Latch



Medium duty tubular mortice latch with 'anti-shim' plunger. Latch retracts by turning inside handle freely, or the outside handle after code input.

AHM-CL510 / CL515 BB
Back to Back Option



Medium duty tubular mortice latch. Two coded plates for installation on both sides of the door. Provides coded access in both directions.

AHM-CL520 / CL525
Mortice Lock



Euro profile mortice sash lock with deadbolt and latchbolt. With the deadbolt thrown it denies access to code users.

FEATURE	DESCRIPTION
Spindle Type	Two part 8mm (5/16") spring loaded spindle
Mortice Latch	Medium duty latch with 'anti-shim' plunger
Mortice Lock	Euro profile mortice sash with deadbolt and latchbolt
Material	Zinc Alloy
Finish	PVD (Physical Vapour Deposition), low maintenance
Finish Colour	Stainless Steel & Polished Brass
Non-handed	Locks will fit doors hung on the left or right
Door Thickness	35mm - 60mm (1 3/8" - 2 3/8")
Codes	2,047 non sequential code combinations available
Code Storage	Single Code
Buttons	12 stainless steel buttons
Fitting Options	Vertical only
Suitable For	Internal and external use
Standards	Suitable for 30 or 60 minute fire doors. Tested in accordance with: BS EN 1634-1:2008

t 02392 389 076

e sales@ahmarra.co.uk

w www.ahmarra.co.uk

ahmarra