

Ahmarra Ironmongery

Pre-Load Electric Strike

FEATURES & BENEFITS

- Operates under pre-load up to 25kg
- Easy field selectable fail safe / fail secure
- Multi voltage 12v-24v
- Full monitoring
- Continuously rated solenoid
- Latch keeper is significantly quieter in operation
- Mounting tabs as standard
- Non handed - field changeable to required configuration



ELECTRICAL

- 10 - 30Vdc
- 250mA @12Vdc - 130mA @24Vdc
- Solenoid rated for continuous use
- Polarity and back EMF protected

MONITORING

- Solenoid monitor - 1 amp NO/NC microswitch
- Door / latch monitor - 1 amp NO/NC microswitch

STANDARDS

- Tested to the highest level of strength and durability in accordance with the requirements of AS4145.2:2008 when used with an approved lockset
- C-tick and CE compliant
- 4-hour fire rating, when used with approved door (in accordance with AS1905.1-2005, Part 1: Fire Resistant Doorsets)

PERFORMANCE

- 680kg (1,500lbs) Static strength rating (UL 1034).
- 200,000 cycles endurance rating @ 25kg pre-load (based on EN12209, Grade Y)
- Suitable for 15mm latch with 3mm door gap

Code	Product
AHM-ES9000	AHM Pre-Load Electric Strike

t 02392 389 076

e sales@ahmarra.co.uk

w www.ahmarra.co.uk

ahmarra