


Severecore™

Severe Duty Door Core



TRIED & TESTED

Severecore™ is a solid three layer particle board, achieving severe duty under the classification standard BS EN 12400:2002.



WHY SPECIFY SEVERECORE™?

- **High Performance** - the engineered performance has been tested to achieve a severe duty rating for durability.
- **Flexibility in Design** - certification covers a wide range of door sizes, fire ratings, glazing and acoustic options.
- **Engineered Materials** - this ensures that the materials within the door construction are defect free.
- **Environmentally Friendly** - all materials are FSC® certified and fully sustainable.

Environmental credentials	FSC® certified
Independent third-party certification	BM TRADA
Fire rating	Available in FD30 and FD60
Acoustic rating	Up to 35Rw dB

FD30 Specifications

Weight: 27.3 kg m²
 Width: 44mm
 U-Value (W/km²): 2.0

FD60 Specifications

Weight: 33.5 kg m²
 Width: 54mm
 U-Value (W/km²): 1.8

SUMMARY OF TESTING PROCEDURE	RESULT
BS EN 947, EN948, EN949 and EN950 (classified to BS EN 1192 mechanical strength)	Severe Duty, Class 4
BS EN1191 (classified to BS EN 12400 mechanical durability)	Severe Duty, Class 8, Completed 1,000,000 Cycles
Operating forces evaluated according to PAS 24	

t 02392 389 076

e sales@ahmarra.co.uk

w www.ahmarra.co.uk

ahmarra