


Timbercore™

Severe Duty Solid Timber Door Core

Traditional laminated softwood or hardwood core with MDF facings for internal use or plywood for external applications.



WHY SPECIFY TIMBERCORE™?

- **High Performance** - tested to achieve a severe duty rating for durability.
- **Suitable for External Use** - when faced with plywood.
- **Flexibility in Design** - certification covers a wide range of door sizes, fire ratings, glazing and acoustic options.
- **Environmentally Friendly** - all materials are FSC® certified and fully sustainable.

Environmental credentials	FSC® certified
Independent third party certification	BM TRADA
Fire rating	Available in FD30 and FD60
Acoustic rating	Up to 35Rw dB

FD30 Specifications

Weight: 19.8 kg m²
Width: 44mm
U-Value (W/km²): 1.8

FD60 Specifications

Weight: 24.3 kg m²
Width: 54mm
U-Value (W/km²): 1.6

SUMMARY OF TESTING PROCEDURE	RESULT
Classified to BS EN 1192 mechanical strength	Severe Duty, Class 4
BS EN1191	Severe Duty, Class 8, Completed 1,000,000 Cycles
Operating forces evaluated according to PAS 24	

t 02392 389 076

e sales@ahmarra.co.uk

w www.ahmarra.co.uk

ahmarra